

CLEAR MASTIC ADHESIVE888.702.9915
www.totalwall.com

Multiple Purpose Construction Adhesive.

AMERICA'S EIFS AND STUCCO COMPANY!

Total Wall Clear Mastic #11 is an adhesive for all rigid and semi-rigid insulation materials.

Total Wall Clear Mastic #11 is a high solids 100% acrylic compound, which has low odor, low toxicity and contains no solvents.

Total Wall Clear Mastic #11 produces a permanent superior bond to a wide variety of substrates including wood sheathing, masonry, and gypsum sheathings.

TOTAL WALL
Total Quality. Total Service. Total Satisfaction.

CLEAR MASTIC 11#
PolyStyrene Construction Adhesive

Superior Quality

Total Wall Inc - 888-702-9915
www.TotalWall.com

Features

- Easy to use, premixed in the pail
- Meets VOC, VOS requirements
- Does not create a vapor barrier
- Bonds quickly and permanently
- Environmentally safe, Non-Toxic
- Exterior or Interior use

Coverage

200 to 275 sqft per 5gallon pail on smooth surfaces

150 to 225 sqft per 5gallon pail on rough surfaces

Application

The substrate must be firm, dry and free of loose debris, oils or any substance that would interfere with bond. The substrate should conform to T-Wall Exterior Insulation Finish System Specifications, or Foundation Insulation Specifications. Total Wall Clear Mastic is applied directly out of the 5-gallon pail.

If the Total Wall Clear Mastic is too thick for the application, add a few ounces of water to the pail and mix with a low speed mixer.

Ribbon and Dab Method
Using a steel trowel, apply a 2" wide by 3/8" deep band of Total Wall Clear Mastic around the perimeter of the rigid insulation board. Apply evenly spaced trowel length dabs, 3/8" thick of Total Wall Clear Mastic to the center area of the insulation board. At least 1/3 of the area of the backside of the board should now be covered with Total Wall Clear Mastic. Do not apply adhesive to the edges of the insulation.

Notched Trowel Method
Cover the entire back of the insulation board with Total Wall Clear Mastic using a 3/8" notched trowel. Immediately press the insulation board onto the substrate with firm, even pressure. In rare cases, it may be necessary to temporarily tack or fasten the insulation board to the substrate until the Total Wall Clear Mastic has set.

Handling and Storage

Do not apply to frozen or saturated surfaces. Do not apply if

precipitation is forecast within 8 hours of application. Do not apply if the temperature cannot be maintained above 40F for 24 hours. Shelf life in closed containers is 18-24 months when stored at 50-100F. Keep containers sealed and under cover when not in use.

Maintenance

If an area of Exterior Insulated Finish System (EIFS) that has been adhered with Total Wall Clear Mastic becomes dirty or stained, clean with a mild cleaner solution and low-pressure spray rinse. For scars, broken or damaged areas, repairs should be made with the same EIFS products and Clear Mastic.

Precautions

T-Wall Clear Mastic is an alkaline water based material. Do not ingest. Avoid contact with skin and eyes. In case of contact, flush with water. For

contact with eyes, get immediate medical attention in addition to flushing. Wear safety glasses and protective clothing. Keep out of reach of children and pets



Total Wall
888.702.9915 Phone
888.702.9916 Fax
www.totalwall.com

Technical Data

Flash point	>200 F Seta
Density	8.5 lb/gal
Viscosity	thixotropic paste
pH	9.0 - 9.8
Bond Strength	ASTM C297 (mod)
XPS to concrete block	15.2 psi
XPS to concrete block	15.0 psi *
XPS to plywood	14.0 psi
XPS to gypsum sheathing	16.0 psi
* Note - run after 60 saturated freeze/thaw cycles ASTM C67	