

TOTAL PRIME888.702.9915
www.totalwall.com

High quality, 100% acrylic primer coating.

AMERICA'S EIFS AND STUCCO COMPANY!

Total Prime is a high quality, 100% acrylic primer coating designed to seal and condition a stucco brown coat or EIFS base coat prior to application of Total Wall synthetic finish.

Total Prime is compatible with all Total Wall systems including Hard Coat Stucco, Direct applied Exterior Finish Systems, Insulated Concrete Form Systems and Exterior Insulated and Finish Systems.

- Total Prime can be applied by roller, brush, or sprayer.
- Total Prime will increase the coverage of any synthetic finish and improve color development and texture uniformity.
- Total Prime will improve system performance by filling small surface voids in the base coat and sealing existing hairline cracks.

**Coverage**

- Conditions and seals base coat
- Meets VOC, VOS requirements
- 100% acrylic water-based coating
- Does not create a vapor barrier
- Improves synthetic finish coverage
- Improves texture & color uniformity of finish

Application

Prepare surface by removing any dirt, oils, loose debris, or any other substance that may interfere with bond. A dry surface is preferable, but a slightly damp surface is acceptable. Any cracks greater than hairline should be filled with a paintable grade acrylic or single component urethane sealant and allowed to cure 4 hours before beginning coating. Stir product for one minute with a low speed mixer, or manually stick-stir as desired. Do not beat excessive air into the product. Apply Total Prime by roller, brush, or airless sprayer.

For roller application, a 1/4" nap roller produces good results. The nap thickness can be varied to compensate for the substrate characteristics and the desired coverage. To adjust product workability, thin product with up to 24 ounces of water per 5-gallon pail as needed.

For use a prime coat, apply either one or two 4-8 mil (wet) coats as required.

When spray applying Total Prime, it is suggested the coating be back rolled to achieve best results. Allow Total Prime to dry fully before application of finish coat. Dry-time may take from 4 to 18 hours depending on air and surface temperatures and humidity conditions.

Handling and Storage

Do not apply to frozen or saturated surfaces. Do not apply if precipitation is forecast within

8 hours of application. Do not apply if the temperature cannot be maintained above 40 F for 24 hours. Shelf-life in closed containers is 18 months when stored at 50-100 F. Clean-up with water or soapy water before drying.

Precautions

Total Prime is an alkaline water-based material. Do not ingest. Avoid contact with skin and eyes. In case of contact, flush with water. For contact with eyes, get immediate medical attention in addition to flushing. Wear safety glasses and protective clothing. Keep out of reach of children and pets. For questions or additional information, contact the Total Wall Technical Department.

Maintenance

If damage occurs to an installed system, please contact Total Wall for information on repair.



888.702.9915 Phone
888.702.9916 Fax
www.totalwall.com

Technical Data

Density	11.9 lb./gal
Viscosity	approx. 10,000 cps
pH	9.0 - 9.8
Resin Chemistry	100% acrylic (internally plasticized)
Solids	52%
PVC	55% (calculated)
Pigment	non-chalking, UV rated

Coverage

Stucco Base (brown coat) 150-200 sq. ft./gal
/coat EIFS Base Coat 175-225 sq.